



Adhesion promoters

for self-adhesive materials

Characteristics

- + Available on wide range of substrates (PET, PE & OPP films or AL foils)
- + Thickness range: 8 – 250 µm (0.315 – 9.84 mil)
- + Available in combination with metallized films
- + Coating in full area or in pattern possible
- + Clear optical appearance
- + Ecofriendly product due to low VOC
- + Maximum width: 2.200 mm (86.61 ")

Key Advantages

- + Significant improved adhesive anchorage through Hueck Folien's primer
- + Low coating weight for minimal impact on final product construction
- + 2-sided application of adhesion promoters possible
- + Alternative to TCA treated films
- + Equal performance even on recycled base films
- + Adhesion promoters can be used in combination with other functional / optical coatings

Interested?

We are happy to provide you with detailed advice.

Visit our website!

Reinhard Kammerhuber
Sales Director Labeling

T +43 7269 7570-160
M +43 664 961 78 70
R.Kammerhuber@hueck-folien.at

Joachim Ortner
Sales Manager Labeling

T +43 7269 7570-162
M +43 664 961 78 78
J.Ortner@hueck-folien.at

Johann Hilburger
Sales Manager Labeling

T +49 961 388 337-11
M +49 160 906 138 55
J.Hilburger@hueck-folien.de

