

Supermatt

Printable topcoat

Characteristics



- + Sustainable base film available
- + PPWR: Monomaterial for easy disposal, free of PFAS
- + Available on PET 36 – 100 µm (1.42 – 3.94mil), PP 30 – 60 µm (1.18 – 2.36 mil), PE 85 µm (3.35 mil)
- + Coating width up to 2,200mm (87")
- + Design options: clear, white, silver
- + Gloss level typical values 20° 1,5 / 60° 2,5 / 85° 6,0 on white PE



Key Advantages

- + Excellent thermal transfer printing with a wide range of ribbons
- + Perfect printing and ink drying using conventional and digital printing methods
- + Topcoat with paper like appearance
- + Extreme low gloss level

Interested?

We are happy to provide you with detailed advice.

Visit our website!



Markus Brezina
Sales Director Labeling

T +43 7269 7570-170
M +43 664 961 78 71
M.Brezina@hueck-folien.at

Joachim Ortner
Sales Manager Labeling

T +43 7269 7570-162
M +43 664 961 78 78
J.Ortner@hueck-folien.at

Johann Hilburger
Sales Manager Labeling

T +49 961 388 337-11
M +49 160 906 138 55
J.Hilburger@hueck-folien.de

Doron Yotzer
Sales Manager Labeling

T +43 7269 7570-0
M +43 664 88 69 66 32
D.Yotzer@hueck-folien.at